

DIESEL GENERATOR SET

Model: DY-250D

Rate Power: 250kVA/ 50Hz/ 3 phases

Applications:

Home, Buildings, Hospitals, Train station, Bank, Telecom, Mining, Military, Outdoor projects, etc.

Features and Benefits

- Tightly structure, excellent design and craft
- Excellent cooling system, reliable performance under the harshest conditions (ambient temperature up to 40°C and altitudes up to 1000m)
- Self-diagnostic capability simplifies troubleshooting
- LCD display shows system status setup information



Color choices:







- Automatic voltage regulator protects your sensitive electronics from harmonic distortion and unstable power quality
- Soundproof type: Very quite running: 75±3dB(A) at 23ft(7m) at normal load.
- Enclosed muffler for added quietness
- Service and; maintenance accessible through easy-latch side service door

Generator Data

| Prime Power (kVA/kW) | 250/200 |
|--|--------------------|
| Standby Power (kVA/kW) | 275/220 |
| Rated Frequency (Hz) | 50 |
| Running Noise db(A)/7m (Silent type) | 75±3 |
| Voltage (V) | 220/380 or 230/400 |
| Curent (A) | 330 |
| No.Phase | 3 |
| Silent Type-Dimension (L x W x H) (mm) | 3700*1300*2000 |
| Silent Type-Weight (kg) | 2850 |
| Fuel Tank Capacity (L) | Option |
| Fuel | Diesel |





Engine Specifications

Main features:

Brand: DIANYO

- 6-cylinder, water-cooled, in-line diesel engine.
- Efficient fuel system for max power output and durability.
- Large-capacity air cleaner.
- Cost effective, fuel efficient and reliable performance.
- Functional engine with compact structure.
- Excellent after-sales service and sufficient spare parts supplying.
- Easy installation and ready access for routine maintenance

| Model | DY260D |
|------------------------|-------------------------------------|
| Output Power (kw) | 260 |
| Cylinder No. & Config. | 6, In-line |
| Туре | 4 cycle , Diesel |
| Displacement (liters) | 12.9 |
| Governor | Mechanical type/ Electrical type |
| Engine System (r/min) | 1500 |
| Air intake system | Turbo, Inter-cooled |
| Fuel Consumption (L/h) | |
| Oil Capacity (L) | 33 |
| Compression ratio | 16:1 |

Alternator specifications

Main Features:

- Advanced automatic voltage regulator (AVR) control for trouble-free operation under the most demanding conditions.
- 2/3 pitch winding as standard, to avoid excessive neutral current.
- Single or two bearing construction with dynamically balanced rotor and sealed-for-life bearings.
- Easy access for installation and maintenance.
- IP23 as standard.
- Self-excited control system.
 Resist of corruption of oil and acid.

| Brand | DIANYO |
|-------------------|--------------------------|
| Model | DY-250GB |
| Rated Power (kVA) | 250 |
| Excitation System | Brushless, self-exciting |
| Connection Type | 3 phases, 4 wires |
| Power Factor | 0.8 |
| Regulator type | AVR |
| Protection class | IP23 |
| Insulation class | Н |
| | |





Control Panel System



MEBAY

Main Features:

- Using microprocessor as a core, graphics LCD with big screen and backlight, key touch for operation
- All parameters use digital modulation, with higher reliability and stability
- Built-in speed/frequency detecting units can accurately judge the states such as crank success and over speed

Precision measure and display of:

- Generator voltage
- Generator current
- Generator frequency
- Generator active power (kW)
- Generator inactive power (kW)
- Generator apparent power (kVA)
- Generator power factor
- Generator starts count
- Generator hour count
- Cumulate electric energy (kWh)
- Generator temperature
- Generator pressure
- Start battery voltage

- Security password-protected programming levels
- Power supply range is wide, accommodating to different starting battery voltage environment
- Built-in watch dog can never be dead halt, ensuring smooth program execution
- Modular configuration design, inserted type connection terminals, flush type installation, compact structure, easy installation

Protection:

- Emergency stop
- High water temperature
- Low oil pressure
- Over speed
- Under speed
- Loss of speed signal
- Generator over frequency
- Generator under frequency
- Generator over voltage
- Generator under voltage
- Generator over current
- Fail to start
- Auxiliary inputs

^{*} Reserves the right to change the specifications and designs without notice.

